AddOn Computer
34A Mauchly
Irvine, Ca 92618

Office: 949.861.2800
Fax: 949.861.2812
www.addoncomputer.com

MEDIA CONVERTERS - MEMORY UPGRADES
BATTERIES - NETWORKING TRANSCEIVERS

ADD-DWDMMUX8E-LC

8 Channel DWDM Mux Demux with Express Port

Specifications

Parameters		1x8
Channels		8
Operating Wavelength (nm)		21CH / 22CH / 23CH / 43CH / 44CH / 46CH / 47CH / 48CH
Channel Passband (nm)		0.22
COM→21CH (dB) max		0.66
COM→22CH (dB) max		1.04
COM→23CH (dB) max		1.18
COM→43CH (dB) max		1.13
COM→44CH (dB) max		1.60
COM→46CH (dB) max		1.31
COM→47CH (dB) max		1.50
COM→48CH (dB) max		1.87
COM→Express (dB) max		1.69
Isolation (dB)	Adjacent Channel	29
	Non Adjacent Channel	45
Ripple (dB)		0.2
PDL (dB)		0.11
PMD (ps)		0.08
RL (dB)		45
Fiber Type		SMF-28e With 2.0mm Loose tube
Directivity (dB)		52
Power Handling (mw)		300
Operating Temperature (°C)		0~75
Strage Temperature (°C)		-40~85
19” Rack Mount Package		1U